

## EDS - RECIPIENT ELIGIBILITY LAYOUTS

ACS FIELD	FIELD SIZE	FORMAT	TABLE NAME	FIELD	DESCRIPTION	NOTES
RECIPIENT BASE INFORMATION						pbm00700.dat
SAK Recip	9	Num	T_RE_BASE	SAK_RECIP	Recipient System Assigned Key.	
Recipient ID	12	Char	T_RE_BASE	ID_MEDICAID	Unique Identifier for the recipient. This is the number assigned by ICES.	Recipients with no eligibility within the past 3 years will not be sent.
Recip Last Name	15	Char	T_RE_BASE	NAM_LAST	The last name of a recipient.	
Recip First Name	13	Char	T_RE_BASE	NAM_FIRST	The first name of a recipient.	
Recip Middle Initial	1	Char	T_RE_BASE	NAM_MID_INIT	The middle initial of the recipient.	
Recip Addr Street 1	30	Char	T_RE_BASE	ADDR_STREET_1	The first line of the address where the recipient resides	
Recip Addr Street 2	30	Char	T_RE_BASE	ADDR_STREET_2	The second line of the address where the recipient resides.	
Recip Addr City	15	Char	T_RE_BASE	ADR_CITY	The city where the recipient resides.	
Recip Addr State	2	Char	T_RE_BASE	ADR_STATE	The state where the recipient resides.	
Recip Addr Zip Code	5	Char	T_RE_BASE	ADR_ZIP_CODE	The five character zip code for the recipient.	
Recip Addr Zip Code Ext	4	Char	T_RE_BASE	ADR_ZIP_CODE_4	The zip plus four of the recipient.	
Recip SSN	9	Char	T_RE_BASE	NUM_SSN	The social security number for the recipient.	
Recip Birth Date	8	Date	T_RE_BASE	DTE_BIRTH	The date of birth for the recipient.	
Recip Death Date	8	Date	T_RE_BASE	DTE_DEATH	The date of death for the recipient.	
Recip Sex	1	Char	T_RE_BASE	CDE_SEX	Indicates the sex of the recipient.	
Recip Race	1	Char	T_RE_BASE	CDE_RACE	Indicates the race of the recipient.	
Recip Marital Code	1	Char	T_RE_BASE	CDE_MARITAL	Indicates the marital status of a recipient.	
Recip County	2	Char	T_RE_BASE	CDE_COUNTY	Indicates the county where the recipient resides.	
Recip Alien Indicator	1	Char	T_RE_BASE	IND_ALIEN	Only emergency services provided for illegal aliens. 'I' - illegal, 'L' - legal, 'N' - no	
Recip Ind Active	1	Char	T_RE_BASE	IND_ACTIVE	Indicates if the recipient Medicaid ID is active or purged because of a link. When two Medicaid IDs are linked one of them is no longer valid and will have an 'N' - no. All others are active and will have a 'Y' - yes or a 'P' - RID has changed.	
Case Number	10	Char	T_RE_CASE	NUM_CASE	The ICES case number assigned to the recipient.	
Carriage Return	1	Hex	n/a	n/a	1 byte for return at end of line	
	179					

## EDS - RECIPIENT ELIGIBILITY LAYOUTS

ACS FIELD	FIELD SIZE	FORMAT	TABLE NAME	FIELD	DESCRIPTION	NOTES
<b>RECIPIENT ELIGIBILITY INFORMATION</b>						pbm00710.dat
SAK Recip	9	Num	T_RE_BASE	SAK_RECIP	Recipient System Assigned Key.	
Recipient ID	12	Char	T_RE_BASE	ID_MEDICAID	Unique Identifier for the recipient. This is the number assigned by ICES.	
Elig Effective Date	8	Date	T_RE_ELIG	DTE_EFFECTIVE	The date that medicaid recipient becomes eligible for the corresponding aid category.	
Elig End Date	8	Date	T_RE_ELIG	DTE_END	The date that the Medicaid recipient is no longer eligible for the corresponding aid category.	Rows with end dates > 3 years old will not be sent.
Elig Status	1	Char	T_RE_ELIG	CDE_STATUS1	The status code for the program eligibility segment. A blank means the segment is active and an H means that the segment is history and no longer valid.	H records will not be sent.
Elig Health Program	2	Char	T_PUB_HLTH_PGM	CDE_PGM_HEALTH	Identifies the medical assistance program such as Medicaid, 590, CSHCS, and Arch.	
Carriage Return	1	Hex	n/a	n/a	1 byte for return at end of line	
	41					
<b>RECIPIENT AID CATEGORY INFORMATION</b>						pbm00712.dat
SAK Recip	9	Num	T_RE_BASE	SAK_RECIP	Recipient System Assigned Key.	
Recipient ID	12	Char	T_RE_BASE	ID_MEDICAID	Unique Identifier for the recipient. This is the number assigned by ICES.	
Recip Aid Category	2	Char	T_CDE_AID	CDE_AID_CATEGORY	Identifies the type of aid for which the recipient is eligible.	
Aid Elig Effective Date	8	Date	T_RE_AID_ELIG	DTE_EFFECTIVE	The date that the Medicaid recipient becomes eligible for the corresponding aid category.	
Aid Elig End Date	8	Date	T_RE_AID_ELIG	DTE_END	The date that the Medicaid recipient is no longer eligible for the corresponding aid category.	Rows with end dates > 3 years old will not be sent.
Aid Elig Status	1	Char	T_RE_AID_ELIG	CDE_STATUS1	Identifies whether or not the eligibility aid segment is active. A blank means that the segment is active. An H means that the segment is history and no longer active.	H records will not be sent.
Carriage Return	1	Hex	n/a	n/a	1 byte for return at end of line	
	41					

## EDS - RECIPIENT ELIGIBILITY LAYOUTS

ACS FIELD	FIELD SIZE	FORMAT	TABLE NAME	FIELD	DESCRIPTION	NOTES
<b>RECIPIENT SPENDDOWN LIABILITY</b>						pbm00702.dat
SAK Recip	9	Num	T_RE_BASE	SAK_RECIP	Recipient System Assigned Key.	
Recip ID	12	Char	T_RE_BASE	ID_MEDICAID	Unique Identifier for the recipient. This is the number assigned by ICES.	
Effective Date	8	Date	T_RE_SPEND_LIAB	DTE_EFFECTIVE	The date on which the recipient starts being liab. for spenddown amount.	
End Date	8	Date	T_RE_SPEND_LIAB	DTE_END	The last date a recipient is responsible for spenddown payments. Generally, the range of spenddown liability is 6 months and there may be several spenddown met dates associated with this period.	Rows with end dates > 3 years old will not be sent.
Carriage Return	1	Hex	n/a	n/a	1 byte for return at end of line	
	38					
<b>RECIPIENT SPENDDOWN MET DATE</b>						pbm00720.dat
SAK Recip	9	Num	T_RE_BASE	SAK_RECIP	Recipient System Assigned Key.	
Recip ID	12	Char	T_RE_BASE	ID_MEDICAID	Unique Identifier for the recipient. This is the number assigned by ICES.	
Spenddown Met Date	8	Date	T_RE_SPEND_PAYMENT	DTE_RECEIVED	The date for the calendar month that spenddown was met. Spenddown begins again on the first day of the next calendar month.	Rows with end dates > 3 years old will not be sent.
Carriage Return	1	Hex	n/a	n/a	1 byte for return at end of line	
	30					
<b>RECIPIENT LOCKIN INFORMATION</b>						pbm00730.dat
SAK Recip	9	Num	T_RE_BASE	SAK_RECIP	Recipient System Assigned Key.	
Recip ID	12	Char	T_RE_BASE	ID_MEDICAID	Unique Identifier for the recipient. This is the number assigned by ICES.	
Indicator	1	Char	T_RE_LOCKIN_PERIOD	IND_RESTRICT	Indicates if this is a lockin (I) or lockout (O).	
Provider ID	9	Char	T_PR_PROV	ID_PROVIDER	This is the Provider number that the Recipient is Locked into.	
Claim Type	1	Char	T_RE_LOCKIN_INFO	CDE_CLM_TYPE	This is the claim type the recipient is locked into.	
Provider Type	2	Char	T_RE_LOCKIN_INFO	CDE_PROV_TYPE	This is the provider type the recipient is locked into.	
Provider Specialty	3	Char	T_RE_LOCKIN_INFO	CDE_PROV_SPEC	This is the provider specialty the recipient is locked into.	
Effective Date	8	Date	T_RE_LOCKIN_INFO	DTE_EFFECTIVE	Date that the Lockin became effective.	
End Date	8	Date	T_RE_LOCKIN_INFO	DTE_END	Date that the Lockin restriction ends.	Rows with end dates > 3 years old will not be sent.
Carriage Return	1	Hex	n/a	n/a	1 byte for return at end of line	
	54					
<b>RECIPIENT PMP ASSIGNMENT INFORMATION</b>						pbm00810.dat
SAK Recip	9	Num	T_RE_BASE	SAK_RECIP	Recipient System Assigned Key.	
Recipient ID	12	Char	T_RE_BASE	ID_MEDICAID	(Convert sak_recip to id_medicaid).	

## EDS - RECIPIENT ELIGIBILITY LAYOUTS

ACS FIELD	FIELD SIZE	FORMAT	TABLE NAME	FIELD	DESCRIPTION	NOTES
Service Location	1	Char	T_RE_PMP_ASSIGN	CDE_SERVICE_LOC	Suffix added to the provider number to identify the various locations that a provider does business.	
PMP Enrollment Date	8	Date	T_RE_PMP_ASSIGN	DTE_EFFECTIVE	The effective date when a recipient began utilizing this provider as a PMP. This date can not be prior to the recipient's Medicaid eligibility date.	
PMP Disenrollment Date	8	Date	T_RE_PMP_ASSIGN	DTE_END	The date that the recipient is no longer utilizing this provider as a PMP.	
PMP Program	1	Char	T_RE_PMP_ASSIGN	CDE_HEALTH_SUBPGM	Identifies the program this PMP accepted enrollment of this recipient into: PCCM or RBMC. Managed Care policy states that a PMP can only accept enrollment into one program at a time. The valid values for this field are:	
PMP MCO	9	Char	T_MCO	ID_MCO	Provider ID to uniquely identify a Managed Care Organization (MCO) within the system. This is the RBMC programs MCO, that the PMP is affiliated with. (Convert sak_mco to id_mco by linking to the t_mco table).	Available if MCO sak is not 0.
Region	1	Char	T_RE_PMP_ASSIGN	CDE_STATE_REGION	This is the code that designates the MCO regions that are currently active in the managed care RBMC program.	
PMP Start Reason	2	Char	T_RE_PMP_ASSIGN	CDE_RSN_MC_START	Indicates the reason a recipient's PMP segment for managed care eligibility was started. These codes are carried on table t_re_pmp_reason.	
PMP Stop Reason	2	Char	T_RE_PMP_ASSIGN	CDE_RSN_MC_STOP	Indicates the reason a recipient's PMP segment for managed care eligibility was stopped. These codes are carried on table t_re_pmp_reason.	
Indicator Recipient Letter	1	Char	T_RE_PMP_ASSIGN	IND_RECIP_LTR	This is the indicator to tell whether or not the confirmation letter has been sent to the recipient on this assignment.	
PMP Assignment Date	8	Date	T_RE_PMP_ASSIGN	DTE_ADDED	Date the recipient was assigned to a PMP.	
Provider ID	9	Char	T_PR_PROV	ID_PROVIDER	(Convert sak_prov to id_provider).	
Group Provider ID	9	Char	T_PR_PROV	ID_PROVIDER	(Convert sak_prov_group to id_provider).	Available if prov is a group prov, i.e. if sak_prov_group is not 0.
Carriage Return	1	Hex	n/a	n/a	1 byte for return at end of line	
	81					
<b>RECIPIENT LEVEL OF CARE</b>						pbm00740.dat
SAK Recip	9	Num	T_RE_BASE	SAK_RECIP	Recipient System Assigned Key.	
Recip ID	12	Char	T_RE_BASE	ID_MEDICAID	Unique Identifier for the recipient. This is the number assigned by ICES.	
Level of Care Code	3	Num	T_RE_LOC	CDE_LOC		
Effective Date	8	Num	T_RE_LOC	DTE_EFFECTIVE	Effective Date	

## EDS - RECIPIENT ELIGIBILITY LAYOUTS

ACS FIELD	FIELD SIZE	FORMAT	TABLE NAME	FIELD	DESCRIPTION	NOTES
End Date	8	Num	T_RE_LOC	DTE_END	End Date	Rows with end dates > 3 years old will not be sent.
Carriage Return	1	Hex	n/a	n/a	1 byte for return at end of line	
	41					
<b>RECIPIENT CROSS REFERENCE</b>						pbm00742.dat
SAK Recip	9	Num	T_RE_OLD_PCN	SAK_RECIP	Recipient System Assigned Key.	
Previous Recip ID	12	Char	T_RE_OLD_PCN	ID_MED_RECIP_PREV		
Effective Date	8	Num	T_RE_OLD_PCN	DTE_EFFECTIVE	Effective Date Will always be zero due to no start date	
End Date	8	Num	T_RE_OLD_PCN	DTE_END	End Date (Last date this ID was in effect).	Rows with end dates > 19981231
Carriage Return	1	Hex	n/a	n/a	1 byte for return at end of line	
	38					